

Efficient & Effective

TWIN HEAD CONCRETE GRINDER

Applications:

- Removing paint, pebble Crete in concrete (not epoxy applied), stains, tar, rubbery compounds, mortar dropping and ceramic. tile mortar residue, stencilcrete.
- Changing levels in concrete.
- Not suitable for terrazzo or marble.

Features:

- Ergonomically design allows ease of operation without the directional pull of conventional floor machines.
- Design for both wet and dry applications.
- High wear-resistance Tungsten Carbide Tips.
- Variable speed adjustment throttle.
- Sturdy Built Body for durability.
- Grinding Width of 10" (inches) for job efficiency.
- Diamond stones can be replaceable.
- Not suitable for terrazzo or marble.




Standard Machine complete with 2pcs 10" Grinding Disc



2 x 10" Grinding Disc
- For Rough Grinding

Optional: Metal Bond Diamond



50#

100#

Model	Segments Size	Grit	Working Type
3-T3	3" Ø12 * 12	50# 100#	Dry

Optional: Resin Polishing Pad



Model	Segments Size	Grit	Working Type	
XY-XZ	Diameter Ø3 inch Thickness: 10mm	#50	#100	Dry Polishing
		#200	#400	

Model	TKCG-210
Grinding Width	2 x 10" (250mm)
Grinding Speed (rpm)	400 to 600
Engine	Honda GX-270
Engine Type	Air-cooled Gasoline
Max. Output (HP/rpm)	8.5 / 3600
Starting System	Recoil
Weight (kg)	90
Dimensions (LxWxH) (mm)	1130 x 660 x 930